



Features

- * New digital designing.
- * Using earmuffs headphones to monitor and speak.
- * With individual volume control and automatic squeal function.
- * Have the same access interlocking functions and ensure the channel can match the language one-to-one.
- * With cough eliminating function, when the interpreter cough, it can prevent cough come out.
- * When the speaker speaks too fast, you can press the button "slow" to asked for the speaker to slow down the speed.
- * With indirect translation switch (REPLAY). When the translators can't understand the speakers meaning, he can monitor the transliteration of other translators to translate for the second time.
- * Can be used with the connection of the infra-red language distribution system.
- * Two translators can take turns to use the same translation unit.
- * Can be carried out the function of simultaneous interpretation in 12 languages. (Including the soundtrack channel).

Specifications

Model	TH-0700HY
Mic Impedance	2K
Frequency Response	80-16000Hz
Sensitivity	-46dBV/Pa
Earphone Impedance	16
Earphone Volume	1.5V
Crosstalk	>70dB
Earphone Frequency Response	100-15000Hz
Earphone THD	<0.1%
Earphone S/N Ratio	>70dBA
Dynamic Range	>85dB
Power Supply	24V 80mA
Mic Input	3.5 mm mono Mic input
Earphone Input	3.5 mm stereo earphone input
Output/Input Connector	25 Pins male and female connector
Dimension (WxHxD)	330x200x70mm
Weight	2.2kg